

# HiLight V5+ Safe Light

The HiLight V5+ are the light towers that construction sites, outdoor events and industries around the world have been asking for. These light towers offer the ultimate in fuel economy and reliability. Its LED lighting technology provides extended benefits and represents outstanding value for our customers.

The HiLight V5+ include a HardHat® canopy as standard, which ensures maximum protection of internal parts. This range of light towers is perfect for multiple drop rental applications and providing users a robust and easy-to-transport set of lighting options that match any site requirements. The extended safety features also guarantee the protection of bulbs during transportation.

#### Innovative LED lights

- Unique lens design having a uniform light distribution.
- Right combination of LED chips and LED optics.
- Directional optics are made of glass fibre which offers uniform light distribution.
- Each LED lamp has one concave and one convex lens to ensure even light distribution.
- LED lamps have an aluminium casting which offers heavy duty protection and robustness under intensive use.
- Each LED lamp can withstand baseball impact thrown at a speed of 100MPH



### Robust and durable 1

Legendary HardHat® enclosure made of Polyethylene. The exclusive hinged top panel provides easy access to the engine, generator and electrical components for quick and hassle-free maintenance.

#### **Optional features**


- Controller
- Battery switch
- RCCB
- Mains
- Fire extinguisher
- Cold start\*
- Photocell\*
- Electric winch\*

stworks only with controller















#### High luminosity

The HiLight V5+ comes with 4 LED lamps x 350 W that gives you even more durability and light coverage.



**Lifting hooks** 

CPCB II Compliant

#### <sup>1</sup> Fuel efficiency

The best fuel consumption in its segment with a fuel consumption of 0.9 l/hr, and a maximum run time of 88 hrs.

SAVINGS: 50%

• UP TO 50%

• 1,000 LITERS

EVERY 2,000 HOURS

#### Safe mast +

The vertical mast is extremely stable and quick to operate. This model can be transported with the mast in vertical position.



#### **Quiet operation**

Thanks to its air flow design and the Hardhat<sup>®</sup> canopy, the HiLight V5+ is the most silent Light Tower in its segment with 75 dB(A) as per CPCB II

**→ Fork lift slots** 

**Emergency** switch





#### **Technical Data**

		HiLight V5+
Performance Data		
Rated Frequency	Hz	50
Rated Voltage	VAC	230
Rated Power (PRP)	kW	5
MX Sound Power level (LWA) (measured according to CPCB II)	dB(A)	75
Engine		
Model		Lombardini KD441-GSI2
Rated Net Output (PRP)	kW	6.1
Alternator		
Model		Sincro
Rated output	kVA	4.8
Degree of protection	IP	IP 23
Consumption		
Fuel tank capacity	litre	80
Runtime with lamps ON	hrs	88
Lights		
Floodlights		LED
Wattage	W	4 x 350
Mast		
Type		Manual vertical, 5 section
Rotation	degrees	360
Maximum Height	m	7.5
Dimensions and weight		
Dimensions in transport with tilted towbar (LxWxH)	m	1.95 x 1.10 x 2.50
towbar (LxWxH)		

Light coverage m <sup>2</sup>	5,000 (average 20 luxes)
Lamps	LED
Mast	Vertical Manual
Features	HardHat* canopy

Photos and illustrations contained herein might depict products with optional and/or extra components which are not included with the standard version of the product and, therefore, are not included in a purchase of such product unless the customer specifically purchases such optional/extra components. We reserve the right to change the specifications and design of products described in this literature without notice. Not all products are available in all markets.

## Additional Standard Features

- 4 LED lamps x 350 W
- Directional optics with glass fibre
- LED lamps with one concave and one convex lens
- LED lamps with aluminium casting
- 4 heavy duty stabilizers with level bubble
- Oil drains for serviceability
- User friendly control & power panel:
  - Independent circuit breakers
  - Hour meter & key switch
- 80 liter fuel tank for long run time between fills
- Emergency stop button
- Auxilary power socket of 10A with safety feature of dedicated MCB
- Power selection switch for lights or auxiliary power

#### Contact:

S Kumar: +91 99406 86506, s.kumar@atlascopco.com Prakash Khobragade: +91 93314 11141, prakash.khobragade@atlascopco.com Fenil Shah: +91 70304 64386, fenil.shah@atlascopco.com



#### Atlas Copco India Ltd.



