



Husqvarna K 970 Ring

When you need to make deep cuts fast our K 970 Ring is the answer. It has an exceptionally cutting depth of 270 mm, twice the amount of a traditional power cutter. It has a high cutting capacity, can make deep cuts from one side and is the quickest method for small and medium-sized cuts, as no time is lost on installing rails.



DEEP CUTTING

Thanks to the peripheral drive you can cut far deeper than with a traditional power cutter. The cutting depth of 270 mm is sufficient to cut through a normal wall from one side only.



STURDY AND RELIABLE

Less sensitive to outer conditions and fuel variations, thanks to the cylinder design and muffler with integrated heat deflector.



LONG SERVICE INTERVALS

A strong Poly-V belt combined with our maintenance-free starter DuraStarter™ and efficient filter-system Active Air Filtration™ ensures long service intervals.



LIGHT AND POWERFUL

A light, compact and powerful machine with superior power-to-weight ratio.

Features Husqvarna K 970 Ring

- Optimal ignition timing makes the power cutter start easily in any situation.
- The only time the filter needs to be checked and changed is if you experience lack of power.
- Our two-step filtration system with centrifugal cleaning and a single paper filter increases product life and extends service intervals.
- High power with less fuel
- Our X-Torq® engine produces less emissions, lower fuel consumption and produces more power.
- Our dust-sealed starter, where the return spring and the pulley bearing are sealed, gives a virtually maintenance free starter. Developed with a durable starter cord.
- Our built-in automatic filter compensation maintains high power during the air filter life time.
- EasyStart ensures easier starting by reducing the compression in the cylinder.
- Reduced vibrations in the cutter handle for more comfort and longer operation periods.
- The water adjustment gives an efficient dust management and makes operation easier and more efficient.
- Our virtually maintenance free starter, thanks to the dust-sealed starter and the durable starter cord.
- Provides better transmission of power, less frequent re-tensioning and extended service intervals.

TECHNICAL SPECIFICATION

| | |
|---------------------------------------|-------------------------------------|
| Engine | Air-cooled 2 stroke engine |
| Cylinder displacement | 93.6 cm ³ / 5.71 cu.inch |
| Power output | 4.8 kW |
| Fuel tank volume | 1 lit / 33.8 fl oz |
| Idling speed | 2700 rpm |
| Vibrations front handle | 2.7 m/s ² |
| Vibrations rear handle | 3.4 m/s ² |
| Sound pressure level at operators ear | 104 dB(A) |
| Sound power level, guaranteed (LWA) | 115 dB(A) |
| Blade diameter | 370 mm / 14 inch |
| Max cutting depth | 270 mm / 10.6 inch |
| Weight(excl. cutting equipment) | 13.8 kg / 30.4 lbs |

