



Husqvarna WS 482 HF

WS 482 HF is a very powerful wall saw for cutting reinforced concrete, brick and other building materials, up to 730 mm thickness. The water-cooled electric motor has an unbeatable power-to-weight ratio. This wall saw can be used for all kinds of openings and sawing including stair, bevel and flush cutting. It's easy to assemble, run and transport making your job more comfortable and faster. WS 482 HF can be combined with CS 10, transforming it into a perfect wire saw, or WSC 40, transforming it into a perfect chain saw to finish corners.

Motor

Output shaft RPM, max	1200 rpm
Max spindle torque	230 Nm
Spindle starting torque	230 Nm

Transmission

Number of gearbox speeds	2
--------------------------	---

Sound and noise

Sound power level, guaranteed (LWA)	109 dB(A)
Sound power level, measured	108 dB(A)
Sound pressure level at operators ear	108 dB(A)

Cutting equipment

Arbor diameter	25,4/60 mm
Blade diameter, max	1600 mm
Blade diameter, min	600 mm
Cutting depth, max	730 mm
Starter blade diameter, max	1000 mm

Dimensions

Product size length	2200 mm
Product size width	900 mm
Product size height	800 mm
Weight	28 kg
Weight saw carriage	3.9 kg
Weight saw unit	29.6 kg

Other

Water flow, min	3.5 l/min
Water pressure, max	7 bar
Water temp at min flow, max	25 °C

Articles for WS 482 HF

WALL SAW WS 482 HF w/o blade guard	967 64 67-01
WALL SAW WS 482 HF 800 mm blade guard	967 64 67-02
WALL SAW WS 482 HF 1000 mm blade guard	967 64 67-03
WALL SAW WS 482 HF 800mm 3-psc bg + 840mm 1-psc bg	967 64 67-05
WALL SAW WS 482 HF kit for CS 10	967 64 67-06

Features for WS 482 HF

Increased control

Two driving modes – standard which suits most applications while manual mode can be used in tougher conditions when extra control is needed for a more flexible operation.



Efficient and fast sawing

Blade motor and both feeding motors can be operated individually at the same time with maximum power.



Unbeatable power-to-weight ratio

The powerful motor generates 19 kW to the spindle at 32 A, even though the saw head weighs just 28.0 kg.



Easy to transport and setup

The saw's modular design and even weight distribution make it easy to carry and handle.



Accessories for WS 482 HF



Tracks



One-piece blade guard



Track holder



Template bracket, universal



Mounting bracket, standard



Flange

Check website for more accessories.

Recommended tools for WS 482 HF



W1510



W1515 Z-EDGE



ELITE-CUT W1525



W 1110



W 1120

Brick	● ● ○	● ● ○	● ● ○	● ○ ○	● ● ○
Concrete hard	● ● ●	● ● ●		● ● ○	● ○ ○
Concrete medium	● ● ●	● ● ○	● ● ○	● ● ●	● ● ○
Concrete soft				● ● ●	● ● ●
Highly reinforced concrete	● ● ●	● ● ●	● ● ●	● ● ○	● ○ ○
Reinforced concrete	● ● ●	● ● ●	● ● ●	● ● ●	● ● ○